


Air Conditioning
Technical Data
FDXS-F9, FDXS-F



- > FDXS25F2VEB
- > FDXS35F2VEB
- > FDXS50F2VEB9
- > FDXS60F2VEB

TABLE OF CONTENTS

FDXS-F9, FDXS-F


1	Features	2
	FDXS-F9	2
	FDXS-F	3
2	Specifications	4
	Technical Specifications	4
	Electrical Specifications	5
3	Options	6
4	Dimensional drawings	7
5	Centre of gravity	9
6	Piping diagrams	11
7	Wiring diagrams	12
	Wiring Diagrams - Single Phase	12
8	Sound data	13
	Sound Pressure Spectrum	13
9	Fan characteristics	15

1 Features

1 - 1 FDXS-F9

- Compact dimensions, can easily be mounted in a ceiling void of only 240mm
- Medium external static pressure up to 40Pa facilitates unit use with flexible ducts of varying lengths
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- Low energy consumption thanks to DC fan motor
- Optimised heating solution for your home

1



Fan only



Fan speed steps



Dry programme



Air filter



Weekly timer



Infrared remote control



Wired remote control



Centralised control



Auto-restart



Self diagnosis




Multi model application

1 Features

1 - 2 FDXS-F

- Compact dimensions, can easily be mounted in a ceiling void of only 240mm
- Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- Low energy consumption thanks to DC fan motor
- Medium external static pressure up to 40Pa facilitates unit use with flexible ducts of varying lengths
- Optimised heating solution for your home



Fan only



Fan speed steps



Dry programme



Air filter



Weekly timer



Infrared remote control



Wired remote control



Centralised control



Auto-restart



Self diagnosis



Multi model application

2 Specifications

2-1 Technical Specifications					FDXS25F		FDXS35F		FDXS50F9		FDXS60F			
Power input	Cooling		Nom.		kW		0.036				0.060			
	Heating		Nom.		kW		0.036				0.060			
Dimensions	Unit		Height/Width/Depth		mm		200/750/620				200/1,150/620			
	Packed unit		Height/Width/Depth		mm		274/906/751				266/1,306/751			
Weight	Unit				kg		21				30			
	Packed unit				kg		29				37			
Packing	Weight				kg		-				7		-	
Heat exchanger	Length				mm		500				900			
	Rows		Quantity			3				2				
	Fin pitch				mm		1.5							
	Stages		Quantity			12								
	Tube type				ø7 Hi-XD									
	Fin		Type			Multi slit fin								
Air filter	Type					Removable / washable / mildew proof								
Fan	Type					Sirocco fan								
	Air flow rate		Cooling	High	m³/min	8.7			12.0		16.0			
					cfm	307			424		565			
				Low	m³/min	7.3			10.0		13.5			
					cfm	258			353		477			
				Nom.	cfm	307			338		565			
			m³/min		8.7			11.0		16.0				
			Heating		High	m³/min	8.7			16.0				
				cfm		307			565					
				Low	m³/min	7.3			13.5					
					cfm	258			477					
	Nom.	cfm		282			523							
		m³/min	8.0			14.8								
	External static pressure		Nom.		Pa	30			40					
Fan motor	Model					KFD-280-44-8A			KFD-280-65-8A					
	Speed		Steps			3								
			Cooling	High/ Mediu m/Low	rpm	1,270/1,180/1,090			1,270/1,180/1,080		1,280/1,160/1,040			
						Heating	High/ Mediu m/Low	rpm	1,270/1,180/1,090			1,270/1,180/1,080		1,280/1,160/1,040
Sound power level		Cooling			dBA				53			55		56
		Heating			dBA		53			55		56		
Sound pressure level	Cooling		High/Low		dBA		35/27			38/30				
	Heating		High/Low		dBA		35/27			38/30				
Control systems	Wired remote control					BRC1E52A/B								
Refrigerant	Type					R-410A								
Piping connections	Liquid		OD			6.35								
	Gas		OD			9.5			12.7					
	Drain					VP20 (I.D. 20/O.D. 26)								
	Heat insulation					Both liquid and gas pipes								
Temperature control					Microcomputer control									

Standard Accessories : Installation manual; Quantity : 1;

Standard Accessories : Operation manual; Quantity : 1;

Standard Accessories : Insulation for fitting; Quantity : 1;

Standard Accessories : Sealing pad; Quantity : 1;

Standard Accessories : Clamp metal; Quantity : 1;

Standard Accessories : Drain hose; Quantity : 1;

Standard Accessories : Washer for hanger bracket; Quantity : 8;

Standard Accessories : Sealing material; Quantity : 2;

Standard Accessories : Clamps; Quantity : 6;

2 Specifications

Standard Accessories : Washer fixing plate; Quantity : 4;

Standard Accessories : Screws for duct flanges; Quantity : 1;

Standard Accessories : Air filter; Quantity : 1;

2-2 Electrical Specifications				FDXS25F	FDXS35F	FDXS50F9	FDXS60F
Power supply	Name			VE			
	Phase			1~			
	Frequency		Hz	50			
	Voltage		V	230		220-240	
Current	Nominal running current (RLA) - 50Hz	Cooling	A	0.3		0.5	
		Heating	A	0.3		0.5	

Notes

Operating sound is based on the rear side suction inlet and ESP 40Pa. Operating sound for under side suction inlet: (operation sound for rear side suction inlet) +5dB. However, when installation to which the ESP becomes low is carried out, 5dB or more may go up

When connected with multi-system outdoor unit, refer to the specifications of the multi outdoor unit to be connected.

3 Options

3 - 1 Options

FDXS-F
FDXS-F(9)
FXDQ-A

	Option name	Model name	Status	Available	
				VRV	SA
Individual control systems	Wired remote controller	BRC1D52/BRC1D61(1)/BRC1E51A	EXIST	o	o
	Simplified remote controller	BRC2E52C (3)	EXIST	o	o
	Stylish remote controller	BRC3E52C (3)	EXIST	o	o
	Remote control for hotel use	BRC3E52C (3)	EXIST	o	o
	Wireless remote control (H/P)	BRC4C65	EXIST	o	o
Centralised control systems	Central remote control	DCS302CA51/DCS302CA61(1)	EXIST	o	o
	Unified on/off control	DCS301BA51/DCS301BA61(A)	EXIST	o	o
	Schedule timer	DST301BA51/DST301BA61(1)	EXIST	o	o
	Residential central remote control	DCS303A51(1) (2)	EXIST	o	o
Other options	Adaptor for wiring	KRP1B56	EXIST	o	o
	Wiring adaptor for electrical appendices 1	KRP2A53	EXIST	o	o
	Wiring adaptor for electrical appendices 2	KRP4A54	EXIST	o	o
	Remote sensor	KRC501-4B	EXIST	o	o
	Installation box for adapter PCB	KRP1BA101	EXIST	o	o
	Electric box with earth terminal - 2 blocks	KJB212AA	EXIST	o	o
	Electric box with earth terminal - 3 blocks	KJB311AA	EXIST	o	o
	Noise filter (for electromagnetic interface use only)	KEK26-1A	EXIST	o	o
	External control adapter for outdoor unit (must be installed on indoor unit)	DTA104A53	EXIST	o	-
	Multi tenant	DTA114A61	EXIST	o	-
	Insulation kit for high humidity	KDT25N32/KDT25N50/KDT25N63	EXIST	o	o
	Digital input adaptor	BRP7A54	EXIST	o	o

(1): For DAME only.

(2): For residential use only. Cannot be used with other centralised control equipment.

(3): Included languages are:

Language pack - 1: English, German, French, Dutch, Spanish, Italian and Portuguese.

With PC cable - EKPCAB3 - in combination with the Updater PC software, you can additionally change the language to:

Language pack - 2: English, Bulgarian, Croatian, Czech, Hungarian, Romanian and Slovenian.

Language pack - 3: English, Greek, Polish, Russian, Serbian, Slovak and Turkish.

(4): Only possible in combination with simplified remote control BRC2/3E52C.


(5): Requires installation box for adaptor PCB.

3D086534C

4 Dimensional drawings

4 - 1 Dimensional Drawings

FDXS25-35F




Note:

1. In case of back-suction, mount chamber cover to bottom side of the unit.
2. In case of bottom-suction, mount chamber cover to back side of the unit.
3. Location of unit's name plate: control box cover.
4. Mount the air filter at the suction side. (Use an air filter whose dust collecting efficiency is at least 50% in a gravimetric technique.) It can not be equipped with air filter (accessory) when connecting duct to suction side.

1	Liquid pipe connection	Φ 6.4 Flare connection
2	Gas pipe connection	Φ 9.5 Flare connection
3	Socket for drain	VP 20 (ID: Φ 25, ID: Φ 20)
4	Drain hose (accessory)	ID Φ 25 (Outlet)
5	Control box	
6	Transmission wiring	
7	Power supply connection	
8	Suspension bracket	
9	Air filter (accessory)	

3D081343

FDXS50F9




Note:

1. In case of back-suction, mount chamber cover to bottom side of the unit.
2. In case of bottom-suction, mount chamber cover to back side of the unit.
3. Location of unit's name plate: control box cover.
4. Mount the air filter at the suction side. (Use an air filter whose dust collecting efficiency is at least 50% in a gravimetric technique.) It can not be equipped with air filter (accessory) when connecting duct to suction side.

1	Liquid pipe connection	Φ 6.4 Flare connection
2	Gas pipe connection	Φ 12.7 Flare connection
3	Socket for drain	VP 20 (ID: Φ 25, ID: Φ 20)
4	Drain hose (accessory)	ID Φ 25 (Outlet)
5	Control box	
6	Transmission wiring	
7	Power supply connection	
8	Suspension bracket	
9	Air filter (accessory)	

3D085963

4 - 1 Dimensional Drawings

FDXS60F

Note:

1. In case of back-suction, mount chamber cover to bottom side of the unit.
In case of bottom-suction, mount chamber cover to back side of the unit.
2. Location of unit's name plate: control box cover.
3. Mount the air filter at the suction side. (Use an air filter whose dust collecting efficiency is at least 50% in a gravimetric technique.) It can not be equipped with air filter (accessory) when connecting duct to suction side.


1	Liquid pipe connection	Ø 6,4 Hare connection
2	Gas pipe connection	Ø 12,7 Hare connection
3	Socket for drain	VP 20 (ID Ø 26, ID Ø 20)
4	Drain hose (accessory)	D Ø 25 (Buckle)
5	control box	
6	Transmission wiring	
7	Power supply connection	
8	Suspension bracket	
9	Air filter (accessory)	

3D081360

5 Centre of gravity


5 - 1 Centre of Gravity

FDXS25-35F



4D081337

FDXS50F9




4D085964

5 Centre of gravity

5 - 1 Centre of Gravity

5

FDXS60F




4D081339

6 Piping diagrams

6 - 1 Piping Diagrams


FDXS-F(9)



4D081335C

7 Wiring diagrams

7 - 1 Wiring Diagrams - Single Phase


FDXS-F

3D080361D

8 Sound data


8 - 1 Sound Pressure Spectrum

FDXS20-25F




NOTES:

1. OPERATION NOISE DIFFERS WITH OPERATION AND AMBIENT CONDITIONS.
2. THE OPERATING SOUND IS BASED ON THE REAR SIDE SUCTION INLET AND THE EXTERNAL STATIC PRESSURE 40Pa.




3D081403A

FDXS50F9



NOTES:

1. OPERATION NOISE DIFFERS WITH OPERATION AND AMBIENT CONDITIONS.
2. THE OPERATING SOUND IS BASED ON THE REAR SIDE SUCTION INLET AND THE EXTERNAL STATIC PRESSURE 40Pa.





3D085962A



8 Sound data

8 - 1 Sound Pressure Spectrum

FDXS60F



NOTES:
1. OPERATION NOISE DIFFERS WITH OPERATION AND AMBIENT CONDITIONS.
2. THE OPERATING SOUND IS BASED ON THE REAR SIDE SUCTION INLET AND THE EXTERNAL STATIC PRESSURE 40Pa.




3D081405A

9 Fan characteristics


9 - 1 Fan Characteristics

FDXS25-35F



3D081327B

FDXS50F




3D085960B

9 Fan characteristics


9 - 1 Fan Characteristics

FDXS60F



3D081329B

Daikin Europe N.V. Naamloze Vennootschap - Zandvoordestraat 300, B-8400 Oostende - Belgium - www.daikin.eu - BE 0412 120 336 - RPR Oostende



EEDEN

XXX-06/16



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.